

NOR|Strato

Pack Flute

No.1 May 2020

Basis Werte / values	ISO	Einheit / unit	
Flächengewicht/ Grammage	536	g/m ²	62
Feuchte/Moisture	287	%	8,0
Reißlänge (längs) / Breaking strength m.d.	1924	N	50
Reißlänge (quer) / Breaking strength c.d.	1924	N	17
Durchreißwiderstand längs / Tear index m.d	1974	Nm ² /kg	4,8
Durchreißwiderstand quer / Tear index c.d.	1974	Nm ² /kg	5,8
Bertsdruck / burst	2758	kPa	105
Specific volume / Specific volume	534	cm ³ /g	1,58
Rauigkeit Bendtsen / Roughness Bendtsen	8791-2	ml/min.	350
Weisse / Brightness	2470-2	D65/10° %	60
CIE L	5631-2	D65/10°	83,5
CIE a	5631-2	D65/10°	-0,3
CIE b	5631-2	D65/10°	3,0

Bei den Daten handelt es sich um Durchschnittswerte, die entsprechend den üblichen Fertigungstoleranzen, nach oben und unten schwanken / data are production average values. There is an variability according to the industry common production deviations.

Kombinationswellpappenstoff aus Recyclingfaser für Fein- und Feinstwellen, als Liner und Wellenstoff zu verwenden, maximale Rollenbreite 2100mm / recycled fiber based wavelinerpaper for fine flutes, usable as liner and fluting, maximum reel width 2100mm

Zertifikate / certificates

für den Lebensmitteldirektkontakt von Lebensmitteln, die keinen Migrationstest benötigen (trockene Lebensmittel) geeignet / intent to come in contact with foodstuffs for which migration tests are not requested (dry foods) EC no.1935/2004, direct. 80/590/EEC, direct. 89/109/EEC

